

Wide Format Dual Hot & Cold Laminators

Freestanding laminators have been designed to be fast and easy to use

Save time and money by using a freestanding laminator for quick and professional large format lamination

FEATURES & BENEFITS



- **Ranges**
Laminates pressure sensitive and thermal films
Variable widths to fit your needs : 41" RSH-1050, 45" RSH-1151 and 65" RSH-1651 wide
- **Convenient**
Auto grip shafts for easy materials handling
High quality silicone rubber rollers for both thermal or cold lamination applications
- **Versatility**
Designated controls for temperature and speed help deliver perfect finish, combined with silicone rubber rollers
- **Quality**
Digital controls for temperature and speed help deliver a perfect finish



PremierGraphics
GROUP, INC.
www.premiergraphicsgroup.com

8751 - 162nd Lane NW • Ramsey, MN • 55303
Phone: 763.241.7441 • Fax: 763.274.0131 • Toll-Free: 888.341.1456



Model	RSH-1050	RSH-1151	RSH-1651
Power Supply	AC 220 – 240/50 -60Hz Single Phase	AC 220 - 240V/50 - 60Hz Single Phase	AC 220 - 240V/50 - 60Hz Single Phase
Power Consumption	3000W	3300W	3300W
Max Laminating Width	41(in) / 1050(mm)	45(in) / 1150(mm)	65(in) / 1650(mm)
Max Laminating Speed	Hot 6.6(ft/min) / 2(m/min) Cold 3.3(ft./min) / 1(m/min)	Hot 9.8(ft/min) / 3(m/min) Cold 13.1(ft./min) / 4(m/min)	Hot 9.8(ft/min) / 3(m/min) Cold 13.1(ft./min) / 4(m/min)
Film Thickness	1 - 10(mil) / 25 - 250(mic)	1-10 (mil) / 25 - 250(mic)	1 - 10 (mil) / 25 - 250(mic)
Ready Time	25min	20min	40min
Heating Method	Hot Roller	Hot Roller	Hot Roller
Driving Motor	DC Geared Motor	DC Geared Motor	DC Geared Motor
Max Temperature	Digital up to 320°F (160° C)	Digital up to 320°F (160° C)	Digital up to 320°F (160° C)
Speed Control	Digital (micom) 9 Settings	Digital (micom) 9 Settings	Digital (micom) 9 Settings
Transport Type	4 Roller	4 Roller	4 Roller
Auto Off/Standby	Yes	Yes	Yes
Cooling System	2 Blower	2 Blower	3 Blower
Cross Cutter	Yes	Yes	Yes
Film Core Size	Yes	Yes	Yes
Hot Lamination	Auto Grip 2.25", 3"	Auto Grip 2.25", 3"	Auto Grip 2.25", 3"
Cold Lamination	Yes	Yes	Yes
Mounting	Yes	Yes	Yes
Remote	Yes	Yes	Yes
Foot Pedal	Up to 5/8" (15mm)	Up to 5/8" (15mm)	Up to 5/8" (15mm)
Reverse	Yes	Yes	Yes
Unit Weight	Yes	Yes	Yes
Unit Dimensions (W x D x H)	366(lbs) / 165(kg)	373(lbs) / 169(kg)	538(lbs) / 254(kg)
Carton Weight	55 x 25.5 x 47.5(in)	59 x 25.5 x 47.5(in)	77 x 25.5 x 47.5(in)
Carton Dimensions (W x D x H)	1400 x 650 x 1210(mm) 584(lbs) / 265(kg)	1500 x 650 x 1210(mm) 618(lbs) / 280(kg)	1960 x 650 x 1210(mm) 836(lbs) / 379(kg)
Warranty	61.5 x 35.5 x 57.5(in) 1560 x 900 x 1460(mm) 1 Year Parts & Labor (Roller 6 Months)	65.5 x 35.5 x 57.5(in) 1660 x 900 x 1460(mm) 1 Year Parts & Labor (Roller 6 Months)	86 x 35.5 x 57.5(in) 2190 x 900 x 1460(mm) 1 Year Parts & Labor (Roller 6 Months)

Specifications are subject to change.